

## Przewody pneumatyczne - nylon

Nylon - pochodzenie europejskie			Maksymalne
∅	Kolory		ciśnienie pracy
zew/wew	Biały	Niebieski	[bar]
4/2	PNL/PA6/E/04020/BA	PNL/PA6/E/04020/NB	67
4/3	PNL/PA6/E/04030/BA	PNL/PA6/E/04030/NB	53
5/3	PNL/PA6/E/05030/BA	PNL/PA6/E/05030/NB	60
6/4	PNL/PA6/E/06040/BA	PNL/PA6/E/06040/NB	67
8/5	PNL/PA6/E/08050/BA	PNL/PA6/E/08050/NB	73
8/6	PNL/PA6/E/08060/BA	PNL/PA6/E/08060/NB	40
10/8	PNL/PA6/E/10080/BA	PNL/PA6/E/10080/NB	40
12/6	PNL/PA6/E/12060/BA	PNL/PA6/E/12060/NB	-
12/10	PNL/PA6/E/12100/BA	PNL/PA6/E/12100/NB	33
15/12	PNL/PA6/E/15120/BA	PNL/PA6/E/15120/NB	33
16/14	PNL/PA6/E/16140/BA	PNL/PA6/E/16140/NB	20



- *Maksymalne ciśnienie pracy przy 23°C*